

Junction boxes 1014 - 1015 - 5016

The original ...

... since 1966 - with improved geometry for installation in combustible walls and cavity walls



155 011 047 - 1014



155 011 247 - 1015



155 011 447 - 5016

The tried and tested junction box for every type of wall

Their robust design makes the boxes ideal for concrete construction.

Thanks to their large installation depth, the large volume and the high number of pipe feedthroughs, they leave plenty of room for installations.

Pipe feedthroughs

The boxes come with several M20, M25 and M32 pipe feedthroughs on each side.

The pipe feedthroughs have a small groove that fastens to the corrugated tube.

Affixing cover plates

A chuck for mounting the supplied threaded rod, which enables the mounting of all standard cover plates, is located at the bottom of the box.

Glow wire testing

All boxes meet the glow wire test (GWT) up to 850°C according to EN 60670.

They are thus suitable for concrete, masonry as well as wooden and hollow walls.

Colour, material

Dark grey, HDPE (halogen free), flame retardant.

Item No.	Ammer No.	Units	Description	Dimensions (mm, LxWxD)	Feedthroughs
155 011 047	1014	54	Junction box, GWT 850°C	82 x 82 x 70	20x ø20 / 10x ø25 / 3x ø25 / 3x ø32
155 011 247	1015	45	Junction box, GWT 850°C	82 x 82 x 80	20x ø20 / 10x ø25 / 3x ø25 / 3x ø32
155 011 447	5016	54	Junction box, GWT 850°C	82 x 82 x 70	20x ø20 / 10x ø25 / 3x ø25 / 3x ø32



Glattalstrasse 525 · CH-8153 Rümlang · Tel +41 44 817 24 10 · info@ammer.ch · www.ammer.ch

Ammer AG is a member of the POLYVERIX Group www.polyverix.ch